



FABER CHIMICA S R L  
Campo dell' Olmo - 60044 Faberiano (An) Italy  
Tel: +39 0732.627178 Fax: +39 0732.22935  
[www.faberchimica.com](http://www.faberchimica.com)

## P 147

### Stain, Salt & Water-Repellent

### Impregnator For Polish, Honed & Flamed Surfaces

#### Description

P 147 is water-repellent and stainproof very effective with a final wet look. It can be used for the treatment of marbles, granites, agglomerates, stones, when you want to obtain a brighter colour and in the meantime have water/oil properties. The material treated with P 147 gets a warm colour shade and the natural veins are extremely visible.

#### Application

Apply the product with a lambswool or a brush, on finely honed surfaces apply a few product with a cloth or a lambswool avoiding excesses. Let the product penetrates into the material for few seconds or minutes depending on the type of finishing. Remove (if any) all excesses with a cloth and let it dry. The product can be applied both on interior and exterior surfaces.



#### Maintenance

For periodic maintenance of interior surfaces, mop the surface with a neutral pH cleaner like our NEUGEL.

#### Caution

Flammable product. Provide adequate ventilation when used in confined spaces. Avoid sources of heat and flame. Protect eyes and skin from contact. Do not ingest.

#### Fortuitous leakage and waste disposal method

In case material is released or spilled, clean up the most of the product. Absorb all residues with sand, sawdust etc. Store the residue in metal tank and call for a specialized company.

#### Coverage

POLISHED MATERIALS : 25 - 30 sq.m./lt.

HONED MATERIALS : 20 - 25 sq.m./lt.

FLAMED MATERIALS : 15 - 20 sq.m./lt.

Storage : Keep the container closed and store in a cool and dry place.

Shelf life : 1 - 2 years in original sealed packing.

Packing : 1 lt. bottle(12 per carton) – 5 lt. tin(4 per carton) 10 lt. cans – 25-60 L. drums

#### Technical Data

Appearance : Limpid liquid

Colour : Clear to amber

Odour : Solvent

pH : N/A

Spec. gravity (20°C) : 0,850 gr./cc

Flashing point (ASTM D 56) : 43°C

Marble & Granite Stone Care Ltd.  
Rm. 903, Omega Plaza, 32 Dundas Street, Kowloon, H.K.  
Tel: (852) 2391 0521 Fax: (852) 2789 1678  
[www.mgstonecare.com.hk](http://www.mgstonecare.com.hk)